

MASTER Value LEDtube Universal T8 - 1500 mm

Ballast Compatibility



KEY

	Ballast is compatible
*	Ballast is compatible, light output may differ >10% compared to specifications
**	Ballast is compatible, light output may differ >20% compared to specifications
Dim	Ballast is compatible and conditional released for dimming
	Ballast is not compatible

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



			MAS LEDtube VLE UN 1500mm UO 23W8xx T8
			Product reference number: 9290029973 / 871951431674400 9290029974 / 871951431676800 9290029975 / 871951431678200
			AC (50Hz) on HF Ballast Compatible
Ballast type	10nc / Ref. no.	Lamps on ballast	
PHILIPS	HF-B 158 TLD 220-240	9137 001 123	1
	HF-B 158 TLD EII 220-240	9137 001 927	1
	HF-B 258 TLD 220-240	9137 001 125	2
	HF-B 258 TLD-D EII 220-240	9137 001 929	2
	HF-E 158 TLD-D	9137 130 389	1
	HF-E 1/2 58 TLD-D II	9137 130 409	2
	HF-E 1/2 58 TLD-D II	9137 130 409	1
	HF-P 154/155 TL5 HO/PL-L III IDC	9137 130 282	1
	HF-P 158 TLD EII 220-240	9137 001 912	1
	HF-P 158 TLD-D III IDC	9137 130 318	1
	HF-P 258 TLD EII 220-240	9137 001 916	2
	HF-P 258 TLD-D III IDC	9137 130 319	2
	HF-P Xt 158 TLD EII 220-240	9137 006 179	1
	HF-P Xt 258 TLD EII 220-240	9137 006 180	2
	HF-P 158 TLD 220-240	9137 001 185	1
	HF-P 258 TLD 230-240	9137 001 110	2
	HF-R 258 TLD 220-240	9137 001 119	2
	HF-R 158 TLD EII	9137 006 094	1
	HF-R 258 TLD EII	9137 006 095	2
	HF-RITD 1 28/35/49/54TL5 E+	9137006956	1
	HF-P 158 TLD 230-240	9137001111	1
	HF-RITD 2 28/35/49/54TL5 E+	9137006958	2
	HF-S 158		1
	HF-S 158 TLD-D II	9137 130 322	1
	HF-S 258 TLD-D II	9137 130 325	2
	HF-S 258 TLD-D II HT	9137 006 899	2
	HF-S 158 TLD 220-240	9137 006 319	1
	EB-P 258 TLD ICC 220-240	9137 130 210	2
	HF-P 258 TLD 220-240	9137001206	2
	HF-P 158 TLD 230-240		
OSRAM	QT Deluxe HF 1x58 230-240 DIM		1
	QT Deluxe HF 2x58 230-240 Dim		2
	QT-FIT8 1x58-70		1
	QT-FIT8 2x58-70		2
	QTP8 1x58		1
	QTP8 2x58		2
	QTP-OPTIMAL 1x54-58		1
	QTP-OPTIMAL 2x54-58		2
	QT 1x58 DIM		1
	QT-FIT 5/8 1x54-58		1
	QT-FIT 5/8 2x54-58		2
	QT-FIT8 2x58		2
	QTP 1x58/230-240		1
	QTP 2x58/230-240		2
HELVAR	EL1x58ngn		1
	EL1x58s		1
	EL2x58es		2
	EL2x58HF		2
	EL2x58ngn		2
	EL2x58s		2

MASTER Value LEDtube Universal T8 - 1500 mm

Ballast Compatibility



KEY

	Ballast is compatible
*	Ballast is compatible, light output may differ >10% compared to specifications
**	Ballast is compatible, light output may differ >20% compared to specifications
Dim	Ballast is compatible and conditional released for dimming
	Ballast is not compatible

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



			MAS LEDtube VLE UN 1500mm UO 23W8xx T8
			Product reference number: 9290029973 / 871951431674400 9290029974 / 871951431676800 9290029975 / 871951431678200
			AC (50Hz) on HF Ballast Compatible
TRIDOMIC-ATCO	Ballast type	10nc / Ref. no.	Lamps on ballast
	PC 1/58 T8 INDUSTRY	86 458 037	1
	PC 1x58 T8 PRO Ip	22 185 215	1
	PC 1/58 T8 PRO	22176094	1
	PC 2/58 T8 INDUSTRY	86 458 038	2
	PC 2x58 E011 IDC	22 083 174	2
	PC 2x58 T8 PRO d	22 185 218	2
	PC 1x58 T8 TOP d	22185224	1
	PC 2x58 T8 TOP d	22185227	2
	PCA 1/58 excel one4all	22 085 286	1
	PCA 2x58 EXCEL One4all Ip	28 000 040	2
	PC 1x58 T8 TEC	87500150	1
	PC 1/58 T8 PRO	22176007	1
	PCA 1x58 T8 EXCEL One4all Ip	28000036	1
	PCA 1x58 T8 BASIC Ip	28000043	1
	PCA 1x58 T8 Eco Ip	28000037	1
	PC 2x58 T8 TEC	87500151	2
	PCA 2x58 T8 ECO Ip	28000041	2
VOSSLOH-SCHWABE	ELXc 158,201	188315	1
	ELXc 158,209	188706	1
	ELXc 258,203	188317	2
	ELXc 258,210	188707	2
	ELXc 258,219	188871	2
	ELXe 258,222	188130	2
	ELXe 258,222	188130	1
	ELXe 158,524	188024	1
BAG-HUECO	BCD58,1F-01/220-240/1-10V	1009 7145	1
	BCS58,1FX-11/220-240	1007 7592	1
	BCS58,2FX-11/220-240	1007 7593	2
	BCS58,2SX-01/220-240	1005 1003	2
	D 58,1-23021 E	166072	1
	D 58,2-23021 E	166082	2
	SCS58,2SR-11/220-240	166272	2
	BCS58,1SR-01/220-240	10051002	1
	SCS58,1S-01/230-240	166352	1
	ECS58,2SR-01/220-240	167172	2
TriLux	D58,1-23021E		1
	DD58,1-23031E		1
	D58,2-23021E		
May + Christie	MCU 158		1
	MCU 258		2
Others	Direct mains		
	Electro Magnetic Ballast		

General notes Philips MASTER Value LEDtube Universal

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.

Please note that Philips LEDtubes InstantFit T8 are only tested with HF ballast on AC operation. The performance of Philips LEDtubes InstantFit T8 on HF ballasts with DC operation is not tested and is therefore not guaranteed.

Philips LEDtube InstantFit range is designed to work on HF ballasts only. For EM ballasts or direct mains connection, please contact a Signify sales representative for more information on our EM/Mains compatible range. This document is for information purposes only and must be treated as recommendation. Signify will not accept claims for any damage caused by not implementing the recommendations in this document. Signify does not accept any responsibility, warranty or liability when using Philips LEDtubes with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Signify aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips LEDtube. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming a LEDtube: Ballast types indicated in this list with DIM are conditional released by Signify to offer dimming functionality. Please note that the dimming curve of the LEDtube might differ from the curve of a fluorescent lamp. All other Philips LED tubes are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non dimmable product in a dimmable application, warranty does not apply.