

Philips CorePro LED PLC 9.5W 4P G24q-3

Ballast Compatibility



KEY

	Ballast is compatible
(!)	Do not use in closed luminaires
*	Ballast is compatible, light output may differ >10% compared to specifications
**	Ballast is compatible, light output may differ >20% compared to specifications
	Ballast is not compatible

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions

			CorePro LED PLC 9.5W 4P G24q-3
			Model number / EOC code: 9290037580/9290037581
			AC (50Hz) on HF Ballast Compatible
	Ballast type	10nc	Lamps on ballast
PHILIPS	HF-P 226 PL-T/C III	9137006488	2
	HF-P 126 PL-T/C III	9137006487	1
	HF-P 1 22-42 PL-T/C/L/T5C EII	9137006307	1
	HF-P 2 22-42 PL-T/C/L/TL5C EII	9137006308	2
	HF-S 226 PL-T/C II SR	9137130356	2
	HF-S 226 PL-T/C/L/TL5C II SR	9137130356	2
	HF-S 126 PL-T/C/L/TL5C II SR	9137130357	1
	HF-P 2 26-42 PL-T/C 220-240	9137001950	2
	EB-C 126 PL-T/C 220-240V 50/60Hz	9137131988	1
	EB-C 226 PL-T/C 220	9137131989	2
	HF-P 1/226 PL-T/C III 220-240V 50/60Hz	9137006488	1
	HF-P 1/226 PL-T/C III 220-240V 50/60Hz	9137006488	2
	HF-S 1/2 26 PL-T/C II SR 220-240V 50/60Hz	9137130356	1
	HF-S 1/2 26 PL-T/C II SR 220-240V 50/60Hz	9137130356	2
	HF-R 1 26-42 PL-T/C EII	9137006266	1
	HF-Ri TD 2 26-42 PL-T/C E+	9137006848	2
	HF-Ri TD 1 26-42 PL-T/C E+	9137006847	1
	HF-R TD 1 26-42 PL-T/C EII 220-240	9137006258	1
	HF-P 126 PL-T/C 220-240	9137001100	1
	HFP 226	4411347303 31	2
EB-P 126 PLT/C ICC 220-240V 50/60Hz	9137100654	1	
HF-P 1 26-42 PL-T/C	9137001932	1	
OSRAM	QTP-M 1x26-42	A6979600455	1
	QTP-M 2x26-32	A6979950455 69799500DG	2
	QTP-M 2x26-32	A6979950455 A69799500DG	1
	QT-M 2x26-42/220-240 S	A52675500DG	2
	QTP-T/E 1x26-42,2x26	A72032500DG	2
	QTP-T/E 1x26-42, 2x26	A72032500DG	1
	QT-ECO T/E 2x26/220-240	A53702300DG	2
	QT-ECO 1x26/220...240 S	A48946102DG	1
	QT-T/E 2x26/230-240		2
	QT-M 1x26-42/220-240 S	A48989E00DG	1
	EZ-T/E 1x26/220-240	AA403410155	1
	Qti-T/E 2x18-42 DIM	AA39453 05BS	2
	QT DALI-T/E 2x26-42/230-240 DIM		2
EZ-T/E 2x26/220-240	AA403470155	2	
VOSSLOH-SCHWABE	ELXc 142.872	188700	2
	ELXc 142.872	188700	1
	ELXc 242.837	188643	2
	ELXs 126.906	188667	1
	CBC-226142	540426	2
	ELXc 142.876	188888	1
ELXc 142.876	188888	2	
ELXc 242.877	188889	2	
TRIDONIC	PC 1/2x26 TC PRO sr	22176417	1
	PC 1/2x26 TC PRO sr	22176417	2
	PC 1/2 x 26-42 TC PRO	22176408	1
	PC 1/2 x 26-42 TC PRO	22176408	2
	PC 2x26-42 TC PRO	22176410	2
	PC 1x26-42 TC TOP	28000075	1
	PC 2x26 TC TOP	28000076	2

Philips CorePro LED PLC 9.5W 4P G24q-3

Ballast Compatibility



KEY

(1)	Ballast is compatible
(1)	Do not use in closed luminaires
*	Ballast is compatible, light output may differ >10% compared to specifications
**	Ballast is compatible, light output may differ >20% compared to specifications
	Ballast is not compatible

This document is for information purposes and must be treated as recommendation. Signify attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions

Ballast type			10nc	Lamps on ballast	CorePro LED PLC 9.5W 4P G24q-3		
BAG-HUECO	BCS42.1/26.2LS-01/220-240		10095045	1	AC (50Hz) on HF Ballast Compatible		
	BCS42.1/26.2LS-01/220-240		10095045	2			
	BCS42.1/26.2QI-01/220-240		10095745	1			
	BCS42.1/26.2QI-01/220-240		10095745	2			
	BCS70.1/42.2Q-01/220-240		10097546	1			
	BCS70.1/42.2Q-01/220-240		10097546	2			
	BCS42.1Q-01/220-240		10097535	1			
	BCD57.1/32.2Q-01/220-240/DALI		10096397	1			
	BCD57.1/32.2Q-01/220-240/DALI		10096397	2			
	BCS42.1/26.2Q-01/220-240		10097545	1			
	BCS42.1/26.2Q-01/220-240		10097545	2			
	HELVAR	EL1/2x18-42TCs				1	
		EL1/2x18-42TCs				2	
EL2x32/42TCs				1	*		
TCI	MBQ 226/2	137968/226		2			
	MBQ 142/2	137968/142		1	** (1)		
	MBQ 242/2	137962/242		1	** (1)		
	MBQ 242/2	137962/242		2			
	BCC 126	137949HTC		1			
HUOCO	EVG-HP 1x/2x 15-42W HC	97545		1	(1)		
	EVG-HP 1x/2x 15-42W HC	97545		2			
OTHER	Direct mains 220-240 ACV						

General notes

Please note that our PhilipsCorePro LED PLC are only tested with HF ballast on AC operation. The performance of PhilipsCorePro LED PLC on HF ballasts with DC operation is not tested and is therefore not guaranteed.

This Philips CorePro LED PLC is designed to work on HF ballasts only. For EM ballasts connection, please contact a Philips sales representative for more information on our EM (2 pin) compatible range

This document is for information purposes only and must be treated as recommendation.

Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications.

Philips will not accept claims for any damage caused by implementing the recommendations in this document.

This document focuses on behaviour of above mentioned Philips LEDtube Philips CorePro LED PLC. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.