



# MASTER LEDtube Universal T8 - 1200 mm



## Ballast Compatibility

### KEY

Ballast is compatible
* Ballast is compatible, light output may differ >10% compared to specifications
Ballast is not compatible
Ballast LEDtube combination not tested

*This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions*



	Ballast type	10nc	Lamps on ballast
VOSSLOH-SCHWABE	ELXc 136.207	188708	1
	ELXc 236.202	188316	2
	ELXc 236.208	188705	2
	ELXe 238.527	188137	2
	ELXe 238.527	188137	1
BAG-HUECO	BCS36.1FX-11/220-240	10077590	1
	BCS36.2FX-11/220-240	10077591	2
	D36.2-23021 E	166132	2
	D 58.1-23021 E	166072	1
	ECS36.2SR-01/220-240	167032	2
TriLux	D36.2-23021 E		2
	D58.1-23021E		1
	DD58.1-23031E		1
Others	EM ballast		1
	Direct Mains (only one single side supply)		1

<b>MASTER LEDtube 1200mm Universal, Instant Fit 2500lm</b>
<b>Model number / EOC code:</b> 9290013361 / 871869670537700 9290013362 / 871869670539100 9290013360 / 871869672853600
<b>AC (50Hz) on HF Ballast Compatible</b>

### General note Philips Master LEDtube Universal T8

**General notes:** Philips LEDtubes Universal T8 are designed to work on HF ballasts, or EM ballast, or direct mains connection.

**For HF ballast connection:** Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.

Please note that Philips LEDtubes Universal T8 are only tested with HF ballast on AC operation. The performance of Philips LEDtubes Universal T8 on HF ballasts with DC operation is not tested and is therefore not guaranteed. This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips LEDtubes with HF ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips LEDtube. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on [www.philips.com/ledtube](http://www.philips.com/ledtube)

**For EM ballasts or direct mains connection:** Please refer to the installation guide.