

LED TUBE T5 HF L8 SHORT 288 4W

Ballast compatibility (288 mm)

■ OK compatible / kompatibel

■ OK* compatible but $\pm 10\%$ luminous flux than claimed value /
kompatibel aber $\pm 10\%$ Lichtstrom als angegebener Wert

■ NO Not compatible / nicht kompatibel

LED TUBE T5 HF L8 SHORT 288 V 4W	
Product EAN10	
LED TUBE T5 HF L8 SHORT 288 4W	
Product EAN10	
4058075823693	
4058075823716	

	Model	EAN / Ref.no	L *	
OSRAM	QT-ECO 1X4-16/220-240 S	A48976F0355	1	OK
	QTP-D/E 1X10-13	A697948O2OL	1	OK
Tridonic	PC 1/2x9-13 TC PRO	22176405	1	OK
	PC 1/2x9-13 TC PRO	22176405	2	OK
	PCA 1X11/13 TC ECO	22185126	1	NO
	PC 1X5-16W BASIC	24138833	1	OK
	PC 1X5-16W BASIC	24138830	1	OK
Vossloh Schwabe	ELXs121.901	188663	1	OK
	ELXs121.904	188664	1	OK
BAG	EBS21.1M-01/220-240	1005 0994	1	OK
	BCS21.1-2Q-01/220-240	1009 7543	1	OK
	BCS21.1-2Q-01/220-240	1010 7543	2	OK
TCI	MBQ 113/2	137968/113	1	NO
	BCC 121 IP54	137969IP21MM	1	OK
	BCC 121 SL.	137944/21H	1	OK
	BCC 121/2 SL.	137944B/21H	1	OK
	BCC 121.	137946HTC	1	OK
	BCC 116/2 SL.	137944/16H	1	OK
	BCC 116	137945HTC	1	OK
	MBQ 213/2	137968/213	2	NO
Mains				NO

Q3. 2025

L*: Lamps on ballast / Anzahl Lampen am Vorschaltgerät
 **: ECG is not released for dimming / EVG ist nicht zum Dimmen freigegeben